

MANUAL CALL POINT (MS)

The manual Call Point is tough, durable & highly visible. Alarm LED/s is provided inside the Call Point to indicate the Alarm condition.

FEATURES :

- Available for flush or Surface Mounting.
- Suitable for majority of conventional Fire Alarm System.

specification

Voltage	18-26 V.D.C.
Alarm Current	30 mA
Weight	540 gm
Dimension (mm)	115 x 90 x 52
Colour	Red
Material of Cons.	MS



MANUAL CALL POINT

The manual Call Point is tough, durable & highly visible. Alarm LED/s is provided inside the Call Point to indicate the Alarm condition.

FEATURES :

- Available for flush or Surface Mounting.
- Suitable for majority of conventional Fire Alarm System.
- Front protection glass cover.
- Unbreakable glass ABS plastic body.

specification

Voltage	18-26 V.D.C.
Alarm Current	30 mA
Weight	140 gm
Dimension (mm)	85 x 85 x 50
Colour	Red
Material of Cons.	FR Polymer ABS



AD-110

SOUNDER (MS)

The Electronic sounder is designed for use within fire alarm systems, security systems and industrial signaling systems. It provides an audio warning which is suitable for place which needs audio indication.

FEATURES :

- 24 / 12 Volt DC operation
- High sound output with low current consumption.

specification

Voltage	20-26 V.D.C.
Alarm Current	180 mA
Weight	565 gm
Dimension (mm)	185 x 125 x 75
Colour	Red
Material of Cons.	MS



SOUNDER

The Electronic sounder is designed for use within fire alarm systems, security systems and industrial signaling systems. It provides an audio warning which is suitable for place which needs audio indication.

FEATURES :

- 24 / 12 Volt DC operation
- High sound output with low current consumption.

specification

Voltage	20-26 V.D.C.
Alarm Current	180 mA
Weight	370 gm
Dimension (mm)	115 x 115 x 75
Colour	Red
Material of Cons.	FR Polymer ABS



REMOTE INDICATING LAMP

The unit is designed to ensure that Alarm Signal can be actually transmitted to all locations. To prevent any missing signal specially for the close room.



AUTO DAILER

Totally Micro controller Based System.
2 - Line, 16 - Character LCD With Backlight.
20 Telephone Number with Speech
20 Seconds pre recorded message.
Telephone Number Check Facility
Keypad Access Code Only After Correct Enter of Existing User Code
Program Mode Can only Be Accessed by the Keypad

