

NETWORK CAMERA


2-LINE NETWORK CAMERA



DS-2CD2510F (1.3MP)
DS-2CD2520F (2.0MP)

Mini Dome Camera

- HD real-time video
- 3D DNR, DWDR, BLC
- Support on-board storage
- IP66
- Vandal-proof
- Mobile Application available



DS-2CD2Q10FD-IW
1MP IR PT Camera


- HD720p video
- Low video streaming
- Pan & Tilt rotation
- Up to 10m IR
- Wi-Fi
- PIR detection
- Support on-board storage



DS-2CD2212-I5 (1.3MP)
DS-2CD2232-I5 (3.0MP)

EXIR Bullet Camera

- HD 720P/Full HD 1080P video
- EXIR: up to 50m visibility
- IP66
- 3D DNR, DWDR, BLC



DS-2CD2942F (-I)(-S)
4MP Mini Fisheye Camera


- 2464x1520 resolution
- Compact design
- Support on-board storage
- IR optional
- Audio/Alarm IO optional



DS-2CD2E10F (-W) (1.3MP)
DS-2CD2E20F (-W) (2.0MP)

Recessed-mount Mini Dome


- HD/Full HD video
- Easy installation
- Support SD storage
- PoE
- Wi-Fi optional



DS-2CD2D10WD
1MP Pinhole Camera

- 1280x720 resolution
- HD720p video
- 3.6mm pinhole lens
- 100dB WDR


4-LINE NETWORK CAMERA



LIGHTFIGHTER

DS-2CD4025FWD-A(P)
2MP Smart IP Box Camera


- 1920x1080 resolution
- Full HD1080p, up to 60fps
- 140dB WDR
- Auto back focus
- (P) P-Iris optional
- Full smart feature-set



DARKFIGHTER


DS-2CD4026FWD-A(P)
2MP Smart IP Box Camera

- 1920x1080 resolution
- Full HD1080p, up to 60fps
- Ultra Low light
- 120dB WDR
- Auto back focus
- (P) P-Iris optional
- Full smart feature-set




DS-2CD4035FWD-A(P)
3MP Smart IP Box Camera

- 2048x1536 resolution
- Real-time video
- 20dB WDR
- Auto back focus
- (P) P-Iris optional
- Full smart feature-set



DS-2CD4065F-A(P)
6MP Smart IP Box Camera

- 3072x2048 resolution
- Up to 25fps video
- WDR
- Auto back focus
- (P) P-Iris optional
- Full smart feature-set



DS-2CD4085F-A(P)
8MP Smart IP Box Camera

- 4096x2160 high resolution
- Full smart feature-set
- Auto back focus (-A)
- P-Iris (-P)



LIGHTFIGHTER

DS-2CD4125FWD-IZ
2MP Smart IP Indoor Dome Camera

- 1920x1080 resolution
- Full HD1080p, up to 60fps
- 140dB WDR
- - 2.8~12mm motorized VF lens
- Vandal-proof
- Up to 30m IR
- Full smart feature-set



DARKFIGHTER

DS-2CD4126FWD-IZ
2MP Smart IP Indoor Dome Camera

- 1920x1080 resolution
- Full HD1080p, up to 60fps
- Ultra low light
- 120dB WDR
- - 2.8~12mm motorized VF lens
- Vandal-proof
- Up to 30m IR
- Full smart feature-set



DS-2CD4135FWD-IZ
3MP Smart IP Indoor Dome Camera

- 2048x1536 resolution
- Real-time video
- 120dB WDR
- - 2.8~12mm motorized VF lens
- Vandal-proof
- Up to 30m IR
- Full smart feature-set



DS-2CD4165F-IZ
6MP Smart IP Indoor Dome Camera


- 3072x2048 resolution
- Up to 25fps video
- WDR
- - 2.8~12mm motorized VF lens
- Vandal-proof
- Up to 30m IR
- Full smart feature-set



DS-2CD4185F-IZ
8MP Smart IP Indoor Dome Camera

- 4096x2160 high resolution
- Full smart feature-set
- 2.8~12mm motorized VF lens
- Up to 30m IR
- Audio/Alarm IO
- Vandal-proof

4-LINE NETWORK CAMERAS




NEW

DS-2CD4665F-IZ(S)(H)

6MP Smart IP Outdoor Dome Camera

- 3072x2048 resolution
- Up to 25fps video
- WDR
- 2.8~12mm motorized VF lens
- IP66 & vandal-proof
- Up to 70m IR
- Full smart feature-set
- (-S) Audio/Alarm IO optional
- (-H) Built-in heater & fan optional



NEW

DS-2CD4685F-IZ(S)(H)

8MP Smart IP IR Bullet Camera

- 4096x2160 high resolution
- Full Smart feature-set
- 2.8~12mm motorized VF lens
- Up to 70m IR
- Vandal-proof & IP66
- Audio/Alarm IO (S)
- Built-in heater (H)



NEW

DS-2CD4312F-PTZ

1.3MP Smart IP Outdoor Dome Camera

- 1280x1024 resolution
- HD720p, up to 60fps
- 2.8~12mm motorized VF lens
- Pan & tilt rotation
- IP66 & vandal-proof
- Full smart feature-set



NEW

DS-2CD4312FWD-PTZ

1.3MP Smart IP Outdoor Dome Camera

- 1280x960 resolution
- HD720p video
- 120dB WDR
- 2.8~12mm motorized VF lens
- Pan & tilt rotation
- IP66 & vandal-proof
- Full smart feature-set



NEW

DS-2CD4324F-PTZ

2MP Smart IP Outdoor Dome Camera

- 1920x1080 resolution
- Full HD1080p video
- 2.8~12mm motorized VF lens
- Pan & tilt rotation
- IP66 & vandal-proof
- Full smart feature-set



NEW

DS-2CD4332FWD-PTZ

3MP Smart IP Outdoor Dome Camera

- 2048x1536 resolution
- 120dB WDR
- 2.8~12mm motorized VF lens
- Pan & tilt rotation
- IP66 & vandal-proof
- Full smart feature-set

6-LINE NETWORK CAMERAS



DARK FIGHTER

DS-2CD6026FHW (0733mm)

Smart IP Box Camera

- 1920x1080 resolution
- Full HD1080p, up to 60fps
- Ultra low-light
- 07~33mm super large aperture VF lens included
- ABE optional (-A)
- 120dB WDR
- Supports ANPR
- *customization process required



DS-2CD6124FWD-IZ/H

2.3MP Heat Mapping Intelligence Pro Camera

- 1920x1200 resolution
- 120dB WDR
- Up to 30m IR
- Support on-board storage
- Vandal-proof
- Heat mapping analysis



DS-2CD632F-I (S)(V)

12MP Fisheye Network Camera

- 360° panoramic view
- Up to 4000x3072 resolution, 20fps
- ePTZ control, up to 1600x1200 resolution
- Support heat mapping analytic
- Support people counting (2015.07)
- On-board hardware de-warping
- Support software de-warping (via iVMS5200P)
- Audio/Alarm IO (-S)
- Outdoor version: IP66 & Vandal-proof (-V)



DS-2CD6332FWD-I

3MP WDR IR Fisheye Camera

- Up to 2048x1536 resolution
- 360° panoramic view
- Multiple viewing modes
- Virtual PTZ
- Up to 15m IR
- Support onboard storage
- IP66 model optional
- 120dB WDR



DS-2CD6362F-I

6MP IR Fisheye Camera

- Up to 3072x2048 resolution
- 360° panoramic view
- Multiple viewing modes
- Virtual PTZ
- Up to 15m IR
- Support onboard storage
- IP66 model optional



iDS-2CD6412FWD-30/C

1.3MP WDR People Counting Camera

- 120dB WDR
- Support on-board storage
- Accurate people counting analysis
- Statistic report output



DS-2CD6412FWD-10/-20/-30

1.3MP WDR Covert Camera


- 1280x960 resolution
- 120dB WDR
- Support on-board storage
- Audio/Alarm IO
- Pinhole lens (-10/20)
- Fixed tube lens (-30)
- Up to 8m lens cable



DS-2CD6412FWD-11/-21/-31

1.3MP WDR Dual-lens Covert Camera

- 1280x960 resolution
- 120dB WDR
- Support on-board storage
- Audio/Alarm IO
- Pinhole lens (-11/21)
- Fixed tube lens (-31)
- Support dual lens units
- Up to 8m lens cable



DS-2CD6510-I

1.3MP Outer-vehicle Camera

- 1280x960 resolution
- Up to 20m IR range
- IP68
- Defog
- Analog output support
- 3-axis adjustment



NEW

DS-2CD6510DT-I(O)

DS-2CD6520DT-I(O)

Inner-vehicle Camera

- 1.3/2MP resolution
- IR LEDs
- Reinforcing design
- Vibration-proof
- EN50155, EN61373
- Various connectors
- Rotate mode