

i9-C



➔ Standalone Fingerprint Time and Attendance Terminal

Users : 2200 Fingerprints

Transaction storage : 1,00,000 Logs

Sensor : 500 DPI Optical Sensor

CPU : 32 bit High End Microprocessor

Communication : USB-host , TCP/IP

Identification Speed : ≤ 1 sec

Display : Color TFT

FAR : $\leq 0.0001\%$

FRR : $\leq 1\%$

Card Reader : Inbuilt Prox card reader (optional)

Operating Temperature : $0^{\circ}\text{C} - 45^{\circ}\text{C}$

Operating Humidity : 20% - 80%

Dimension : 21.3 x 14.9 x 4.6 cm

Power : 5V DC , 400mA

Software Features:(eTimeTrack Lite)

- ▶ Desktop Attendance Management Software
- ▶ Support : MS Access / MS SQL Server / Oracle database
- ▶ Parallel logs download optional
- ▶ 150 + Industry standard reports
- ▶ Basic Canteen Management / Visitor Management / Payroll Software
- ▶ Maintain OT Register / Leave Register
- ▶ Schedule Multiple Shifts
- ▶ Generate Analysis Graphs

E9



➔ Standalone IP based Fingerprint Attendance System

Users: 2200 Fingerprints

Transactions: 50,000 Logs

CPU: 32bit Microprocessor

Sensor: 500 dpi Optical Sensor

Identification Speed: ≤ 2 Sec

FAR: $\leq 0.0001\%$

FRR: $\leq 1\%$

Card Reader: Inbuilt Proximity card reader (optional)

Communication: RS232, RS485, TCP/IP

USB-HOST 2.0 Port

Display: Black & White

Operating Temperature: $0^{\circ}\text{C} - 45^{\circ}\text{C}$

Operating Humidity: 20% - 80%

Dimension : 21.3 x 14.9 x 4.6 cm

Power: 5V DC , 400mA

Software Features:(eTimeTrack Lite)

- ▶ Desktop Attendance Management Software
- ▶ Support : MS Access / MS SQL Server / Oracle database
- ▶ Parallel logs download optional
- ▶ 150 + Industry standard reports
- ▶ Basic Canteen Management / Visitor Management / Payroll Software
- ▶ Maintain OT Register / Leave Register
- ▶ Schedule Multiple Shifts
- ▶ Generate Analysis Graphs